# PRO+ 4800

# Credit Card Pay-on-Foot Station







The Pro+ 4800 Series Credit Card Pay-on-Foot Station utilizes an encrypted 2D data matrix barcode and the latest architecture to deliver accelerated system processes and transaction speeds. The Pro+ 4800 Series communicates with Pro+ Software and offers intuitive user guidance through a dynamic color display, motion sensor arming, and voice announcement. The Credit Card Pay-on-Foot Station processes encrypted thermal 2D barcode tickets from the Pro+ 2000/2700 Series Entry Terminals. Payment options include validations and credit card. Mobile and printed barcode validations can be processed through the optional FlexScan QR400® barcode scanner.

### **Features**

- Models include standard magstripe (MSR) or PCI P2PE EMV-ready MSR/chip terminal versions
- Contactless credit card options for NFC, Apple Pay, and Google Pay
- · Thermal receipt printer with auto-retract
- Motion sensor tracking
- · Credential tracking support
- Illuminated components for ease-of-use
- 5.7" color display sunlight readable
- Voice announcement and intercom
- TCP/IP network connectivity
- Remote device programming
- Barcode scanner and Bluetooth options
- LPR-capable
- Supports online and offline fee calculation
- Digital ticket image caputured upon completion of transaction



# PRO+ 4800 Series

# Credit Card Pay-on-Foot Station

# 35.6 [14.02] 47.7 [19.18] CREDIT CARD 00 104.8 [41.27] 131.1 [51.61] 12.7 [5.00] 291 [11.48] [15.49] 19.0 [7.48] 30.0 38.4 [11.81] [15.12] 12 7\* \*Recommendation only. 13.6 Installation requirements may vary. [5.00] [5.35] Curb Face

#### **SPECIFICATIONS**

#### **COMPLIANCE**

#### **RoHS Compliant**

Pro+ 4800 Series equipment does not store credit card data

Meets ADA (Americans with Disabilities Act) and ANSI (American National Standards Institute) requirements

#### **ELECTRICAL**

Power Source: 120 VAC, 60 Hz
Utilization: 10 amp maximum (120V)

#### TIME CONTROL

Real-time clock synchronization with host computer

#### **ENVIRONMENT**

Temperature: -20°F ~ 120°F (-29°C ~ 49°C)

Automatic thermostat-controlled heater included

**Humidity:** 10% ~ 90% (non-condensing)

#### HOUSING

Heavy-duty, 14-gauge steel construction, weather gasketing, lockable door	
Height:	51.6" (131.1 cm)
Width:	14.0" (35.6 cm)
Depth:	19.18"(48.7 cm)
Weight:	140 lbs. (63.5 kg)
Ticket throat:	41.27" (104.8 cm)

Finish (Standard): Textured powder coat finish Amano Light Gray (RAL#7047) Custom color available

#### TICKET READER/ENCODING MECHANISM

Reads all accepted 2D data matrix barcode tickets and validation coupons

Easy ticket jam removal

Encodes encrypted 2D data matrix barcode and transaction data in man-readable text

Vaults used exit tickets

#### RECEIPT PRINTER

High speed thermal line dot

8" thermal paper roll

Auto-retract

#### INTERCOM/VOICE ANNOUNCEMENT

Aiphone LEF series intercom

Standard Voice Announcement

#### **OPTIONAL KITS**

Integrated IP Camera

Integrated FlexScan QR400 Barcode Scanner

Third-party Intercom Mounting

Specifications are approximate and are subject to change without notice.

